



Opal Cleanflush™ Easy Height

4.5/3 litre Vitreous China Wall Faced Close Coupled Toilet Suite for People with Accessible Applications ♿



The polished and streamlined design of the **Opal** range brings style and functionality to the bathroom environment. The added hygiene of the Cleanflush® rimless flushing system makes the range ideal for hospital, aged care and commercial applications where the absolute highest levels of hygiene and rapid cleaning are required. The inclusion of a raised height pan, extra projection and optional armrests make it an ideal solution for aged care applications.

- Pan:** **Opal Cleanflush® Easy Height** 4.5 litre full flush washdown rimless pan with a fully glazed trap.
- Traps:** Universal trap for S or P-trap installations.
- Cisterns:** **Opal Cleanflush®** cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back entry only. **Vandal Resistant Conversion Kit** – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109. Cistern inlet stop valve and inlet flex tube connection is concealed within the cistern and is included. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**
- Buttons:** Round Button - Chrome (supplied). Other button options sold separately. See section 4 - CARE BUTTONS for further details.
- Fixing:** The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.
- Seats:** Includes **Opal II** soft close double flap or normal close single flap seat in Caroma White (W) or Anthracite Grey (AG). See Section 3 - SEATS for further details. **Please note: Opal II double flap seat in Black (BL) available in normal close only.**
- Colour:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.



Uni-Orbital® Connector Setout Range 60mm to 220mm (up to 50mm sideways adjustment)

Opal Cleanflush™ Easy Height Wall Faced Close Coupled Toilet Suite with Opal II Seat

Toilet Suite with Opal II Seat	Code No.	Seat Colour:
4.5/3 litre Back Entry Internal Overflow with Single Flap Normal Close Seat	985400	W or AG
4.5/3 litre Back Entry Internal Overflow with Double Flap Soft Close Seat	985300	W or AG
4.5/3 litre Back Entry Internal Overflow with Double Flap Normal Close Seat	985600	BL

Important
22mm approx. projection from wall
1/2" B.S.P. Nipple
Finished wall

D82 Concealed Fixing Bracket

Note: All height dimensions to underside of pan, make allowance for bedding.
Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.
Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the D82 bracket supplied.